CONCORD PERFORATED WALL PANELS

SPECIFICATION DATASHEET

APPLICABLE CLAUSES: UNICLASS - Ss 25 25 05 Acoustic Panel Systems
CWAS - K13 170 Acoustic Panel Lining

Description: Concord Perforated Wall Panels

System Performance: See Acousticians Report

System Supplier:

Movawall Systems Ltd
Southern Office
63 Barwell Business Park
Leatherhead Road
Chessington, KT92NY
Tel: 0208 391 8750
Email: info@movawall.co.uk
Web: www.movawall.co.uk

Movawall Systems Ltd
Northern Office
Unit 15 Bridge House
Business Centre
Harrow Road
Bolton, BL1 4NH
Tel: 07703 322082
Email: info@movawall.co.uk
Web: www.movawall.co.uk

Movawall Systems Ltd
Scottish Office
Ayr
KA7 1EN
Tel: 01292 265 273
Email: info@movawall.co.uk
Web: www.movawall.co.uk

Batten:	Split batten concealed fixing system
Insulation:	RWA45 Rockwool

Acoustic Performance: Upto Class C – 50mm Airgap

Perforations/Slots:	6mm, 8mm, 10mm & 12mm (Micro-Perforated available on request)
Hole/Slot Centres:	16mm / 32mm / 64mm (project specific size/patterns available)
Finishes:	Birch Plywood, Veneers, LP/HP/CP Laminates, Painted to Colour Ref, Clear Lacquered
Core Material:	Ply or MDF (Standard or FR)
Fire Resistance:	Class1 or Class O (Euro Class B or C) Options Available
Backing Options:	Black open weave/non-woven acoustically transparent
Weight:	Design dependant
Max Panel Sizes:	1200mm (w) x 3000mm (h) Other site specific sizes available on request
Installation:	Pinned & Glued or Split Batten