# SERENITY ACOUSTIC CEILING BAFFLE

## SPECIFICATION DATASHEET

APPLICABLE CLAUSES: UNICLASS - Ss 30 25 22 01 Acoustic Baffle Suspended Ceilings
CWAS – K40 Demountable Suspended Ceilings

Description: Serenity Acoustic Ceiling Baffles

System Performance: NRC 1.0 – 24mm thick

System Supplier:


Movawall Systems Ltd
Southern Office
63 Barwell Business Park
Leatherhead Road
Chessington, KT92NY
Tel: 0208 391 8750
Email: info@movawall.co.uk
Web: www.movawall.co.uk

Movawall Systems Ltd
Northern Office
Unit 15 Bridge House
Business Centre
Harrow Road
Bolton, BL1 4NH
Tel: 07703 322082
Email: info@movawall.co.uk
Web: www.movawall.co.uk

Movawall Systems Ltd
Scottish Office
Ayr
KA7 1EN
Tel: 01292 265 273
Email: info@movawall.co.uk
Web: www.movawall.co.uk


Hanging System: Kits includes Spiral hooks, wire, fixing anchor and easy adjust clamps

Acoustic Performance:

| Acoustic Absorber - Baffles Acoustic Baffle - 24mm | | | | | | | |
|---|---|---|---|---|---|---|---|
| Frequency (Hz) | 125 | 250 | 500 | 1000 | 2000 | 4000 | NRC |
| Baffles 24mm | 0.45 | 0.60 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |

Panelling: Eco-friendly Recycled Compressed Polyester from Plastic Bottles available in 23 different colours

Fire: EN13501-1:2007+A1:2009 Part 1: Classification using data from reaction to fire tests, Class B

Weight: 24mm thick = 4.5kg/m2

Standard Panel Sizes: Variety of shapes and sizes available, see brochure for details at…
Serenity Acoustic Baffles - London Wall

Installation: Standard method suspended via gripple wire method, grid framework optional.