SERENITY ACOUSTIC CEILING RAFT

SPECIFICATION DATASHEET

APPLICABLE CLAUSES: UNICLASS - Ss 30 25 22 70 Raft or Island Suspended Ceilings
CWAS – K40 Demountable Suspended Ceilings

Description: Serenity Acoustic Ceiling Raft

System Performance: NRC 1.0 – 24mm thick

System Supplier:

Movawall Systems Ltd
Southern Office
63 Barwell Business Park
Leatherhead Road
Chessington, KT92NY
Tel: 0208 391 8750
Email: info@movawall.co.uk
Web: www.movawall.co.uk

Movawall Systems Ltd
Northern Office
Unit 15 Bridge House
Business Centre
Harrow Road
Bolton, BL1 4NH
Tel: 07703 322082
Email: info@movawall.co.uk
Web: www.movawall.co.uk

Movawall Systems Ltd
Scottish Office
Ayr
KA7 1EN
Tel: 01292 265 273
Email: info@movawall.co.uk
Web: www.movawall.co.uk

Hanging System: Kits includes Spiral hooks, wire, fixing anchor and easy adjust clamps

Acoustic Performance:

Acoustic Absorber	Acoustic Raft - 24mm						
Frequency (Hz)	125	250	500	1000	2000	4000	NRC
Raft 24mm	0.45	0.85	1.00	1.00	1.00	1.00	1.00

Panelling: Eco-friendly Recycled Compressed Polyester from Plastic Bottles available in 23 different colours

Fire: EN13501-1:2007+A1:2009 Part 1: Classification using data from reaction to fire tests, Class B

Weight: 24mm thick = 4.5kg/m_2

Design Options: Forest, Square (Soft), Rectangle (Soft), Cog, Cloud, Polo, Triangle, Hexagon, Leaf, Pebble, Circle, Ellipse, Diamond, Drop

Standard Panel Sizes: Variety of shapes and sizes available, see brochure for details at…
Serenity Acoustic Rafts - London Wall

Installation: Standard method suspended via gripple wire method, grid framework optional.